

# RPT-1007P-2F-X4 | Industrial 7 Port Fast Ethernet PoE Switch with SFP Ports



## FEATURE HIGHLIGHTS

- 4-port 10/100Tx Ethernet with IEEE 802.3at Compliant PoE+ and 1-port 10/100Tx Gigabit Ethernet and 2-port 100/1000 SFP Slot
- Redundant Power Input Design
- Built-in Relay Output Warning for Power Failure
- IP30 Rugged Metal Case Design
- DIN-Rail Mounting, Wall Mounting
- Operating Temperature -10°C ~ 65°C (-40°C ~ 75°C)

## DESCRIPTION

RPT-1007P-2F-X4 provides 5 Fast Ethernet RJ-45 ports with 4 port PoE and 2 Giga SFP slots for your industrial applications. . The 4 PoE ports provide 30W each RJ45 port feeding to your device. RPT-1007P-2F-X4 also supports redundant power inputs that can be connected simultaneously and back up for power feeding to the switch.

RPT-1007P-2F-X4 is certified CE/FCC and UL61010. For performing in extreme harsh environment, standard operating temperature is -10 to 65 degree and extended operating temperature version between -40 to 75 degree C.

# RPT-1007P-2F-X4 | Industrial 7 Port Fast Ethernet PoE Switch with SFP Ports

## SPECIFICATIONS

Technology	
Standards	IEEE 802.3 10BaseT Ethernet
	IEEE 802.3u 100BaseTX Fast Ethernet
	IEEE 802.3z 1000Base-X Gigabit Fiber
	IEEE 802.3af/at Power over Ethernet
Processing Type	Store and Forward
Protocol	CSMA/CD
Flow Control	IEEE 802.3x flow control, back pressure flow control
Switch Properties	
Switching Fabric (Back-Plane)	5Gbps
Memory Buffer	4Mbits
MAC Table Size	8K
Jumbo Frame	9.6Kbytes
Transfer Rate	14,880pps for Ethernet Port
	148,800pps for Fast Ethernet Port
Interface	
RJ45 Ports	5*10/100Base-T(X) with 4* PoE+
	Auto-Negotiation, Full/Half Duplex, Auto-MDI/MDI-X
PoE Pin Out	V+, V+, V-, V-, for pin 1, 2, 3, 6 (Endspan, MDI Alternative A)
Fiber Port	2*100/1000 SFP slots
Wavelength	Depends on SFP modules
LED Indicators	System: Power 1, Power 2, Fault
	Ethernet ports: On-Link/Flash-data transmitting
	SFP: Link/Active
Relay Contact	PoE : On-connected to PD devices
Relay Contact	24 VDC, 1A resistive
Network Cable	10BaseT: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m)
	100BaseTX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m)

# RPT-1007P-2F-X4 | Industrial 7 Port Fast Ethernet PoE Switch with SFP Ports

## SPECIFICATIONS


Power Requirements	
Input Voltage	Dual 48-55VDC redundant power inputs
Power Connection	1 removable 6-contact terminal block
Overload Current Protection	Present (Slow-Blow Fuse)
Reverse Polarity Protection	Present
System Power Consumption	Max. 9W full loading
PoE Power Output	30Watts max. per PoE port
Max. PoE Power Budget	100W/48VDC; 120W/55VDC
Mechanical Characteristics	
Housing	Metal, IP30 protection
Dimensions (W x H x D)	30 x 142 x 99 mm (1.2 x 5.6 x 3.9 inch)
Weight	Unit weight: 0.58kg (1.27 lb), Shipping weight: 0.724kg (1.59 lb)
Mounting	DIN-Rail Mounting, Wall Mounting
Environmental Limits	
Operating Temperature	Standard: -10°C ~ 65°C (14°F ~ 149°F)
	Extend: -40°C ~ 75°C (-40°F ~ 167°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Ambient Relative Humidity	5 to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Part 15 Subpart B Class A,
	CE EN55022
EMS	CE EN55024
	IEC61000-4-2 (ESD), IEC61000-4-3 (RS), IEC61000-4-4 (EFT),
	IEC61000-4-5 (Surge), IEC61000-4-6 (CS),
	IEC61000-4-8 (Magnetic Field)
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Safety	UL61010-1, UL61010-2-201, ISA 12.12.01
Compliance	NEMA TS2 (ITS) -Extend temperature version
MTBF (Telcordia SR-332, Issue 3, GB, 25°C)	866,424 hrs.

# RPT-1007P-2F-X4 | Industrial 7 Port Fast Ethernet PoE Switch with SFP Ports

## ORDERING INFORMATION

Model name	Description
RPT-1007P-2F-X4	5 Port 10/100/1000 TX with 4 port PoE (30W) + 2 100/1000 SFP ports, 48-55VDC, -10~65°C
RPT-1007P-2F-T-X4	5 Port 10/100/1000TX with 4 port PoE (30W) + 2 100/1000 SFP ports, 48-55VDC, -40~75°C

## DIMENSIONS



Unit: mm (inch)

Din-rail

Wall-mount