



FEATURE HIGHLIGHTS

- 8 x 10/100 Base TX Ports
- 8 PoE Ports comply with IEEE802.3 af/at
- 24~36 VDC Power Boost Design
- IP40 Rugged Aluminum Housing
- Din-rail Type
- Operating temperature -40~75 degree C

DESCRIPTION

RPT-1808P-T-X6SD has 8 x 10/100TX RJ-45 ports for your industrial applications. It has 8 PoE ports comply with IEEE802.3 af/at, and was designed to work in the industrial environment with wide operating temperature, -40~ 75 degree C, with 24~36 VDC power source.

The RPT-1808P-T-X6SD is well-suited for rugged industrial settings and is compatible with DIN-rail mounting for straightforward installation. It is particularly advantageous for power booster design for PoE feature, making installation easy and space-efficient.

Email: sales@sbjlink.com Website: www.sbjlink.com



SPECIFICATIONS			
Technology			
Standards	IEEE 802.3 10BaseT		
	IEEE 802.3u 100BaseTX		
	IEEE 802.3af/at Power over Ethernet		
Processing Type	Store and Forward		
Backplane Bandwidth	1.8Gbps		
Mac Table Size	2K		
Packet Buffer Size	512K		
Interface			
RJ-45 Ports	8x 10/100 BaseT(X) auto negotiation speed		
	Full/Half-duplex mode, and auto MDI/MDI-X connection		
PoE Ports	Port#1 ~ Port#8		
Power			
Input	24~36 VDC		
Consumption	Total <90 Watts with PoE full loaded		
Environment			
Operating	-40°C ~ 75°C		
Storage	-40°C ~ 85°C		
Ambient Relative Humidity	5%~95% non-condensing		
Physical			
Housing	Aluminum housing , Din rail type		
Dimension	48mm x 143mm x 104mm (W x H x D)		
Weight	0.5Kg		

Email: sales@sbjlink.com Website: www.sbjlink.com




SPECIFICATIONS

Regulatory Approvals	
Surge Protection of Power	IEC 61000-4-5 Level X (6KV/4KV) (8/20us)
Surge Protection of Port	IEC 61000-4-5 Level 4 (4KV/4KV) (10/700us)
RS	IEC 61000-4-3 Level 3 (10V/m)
EFI	IEC 61000-4-4 Level 3 (1V/2V)
CS	IEC 61000-4-6 Level 3 (10V/m)
PFMF	IEC 61000-4-8 Level 4 (30A/m)
DIP	IEC 61000-4-11 Level 3 (10V)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free Fall	0.5m



DIMENSIONS

Unit: mm



ORDERING INFORMATION

Model Name	Description	Power input
RPT-1808P-T-X6SD	8 Port Industrial Unmanaged FE PoE+ Switch, Operation temperature -40° C ~ 75° C	24~36VDC

Email: sales@sbjlink.com Website: www.sbjlink.com