

SFP Transceiver Selection

No.	P/N	Speed			Type	Distance	Temp.	DDM	BIDI	Wave Length	
		100M	1G	10G						TX	RX
1	SFPM2	•			Multi-mode	2 KM	0 ~ 70°C	•		1310	1310
2	SFPM2T	•			Multi-mode	2 KM	-40 ~ 85°C	•		1310	1310
3	SFPM5	•			Multi-mode	5 KM	0 ~ 70°C	•		1310	1310
4	SFPM5T	•			Multi-mode	5 KM	-40 ~ 85°C	•		1310	1310
5	SFPM30	•			Single-mode	30 KM	0 ~ 70°C	•		1310	1310
6	SFPM30T	•			Single-mode	30 KM	-40 ~ 85°C	•		1310	1310
7	SFPM60	•			Single-mode	60 KM	0 ~ 70°C	•		1310	1310
8	SFPM60T	•			Single-mode	60 KM	-40 ~ 85°C	•		1310	1310
9	SFPM80	•			Single-mode	80 KM	0 ~ 70°C	•		1310	1310
10	SFPM80T	•			Single-mode	80 KM	-40 ~ 85°C	•		1310	1310
11	SFPM100	•			Single-mode	100 KM	0 ~ 70°C	•		1550	1550
12	SFPM100T	•			Single-mode	100 KM	-40 ~ 85°C	•		1550	1550
13	SFPM120	•			Single-mode	120 KM	0 ~ 70°C	•		1550	1550
14	SFPM120T	•			Single-mode	120 KM	-40 ~ 85°C	•		1550	1550
15	SFPG055		•		Multi-mode	550 M	0 ~ 70°C	•		850	850
16	SFPG055T		•		Multi-mode	550 M	-40 ~ 85°C	•		850	850
17	SFPG2		•		Multi-mode	2 KM	0 ~ 70°C	•		1310	1310
18	SFPG2T		•		Multi-mode	2 KM	-40 ~ 85°C	•		1310	1310
19	SFPG10		•		Single-mode	10 KM	0 ~ 70°C	•		1310	1310
20	SFPG10T		•		Single-mode	10 KM	-40 ~ 85°C	•		1310	1310
21	SFPG30		•		Single-mode	30 KM	0 ~ 70°C	•		1310	1310
22	SFPG30T		•		Single-mode	30 KM	-40 ~ 85°C	•		1310	1310
23	SFPG40		•		Single-mode	40 KM	0 ~ 70°C	•		1310	1310
24	SFPG50		•		Single-mode	50 KM	0 ~ 70°C	•		1550	1550

SFP Transceiver Selection

No.	P/N	Speed			Type	Distance	Temp.	DDM	BIDI	Wave Length	
		100M	1G	10G						TX	RX
25	SFPG50T		•		Single-mode	50 KM	-40 ~ 85°C	•		1550	1550
26	SFPG70		•		Single-mode	70 KM	0 ~ 70°C	•		1550	1550
27	SFPG70T		•		Single-mode	70 KM	-40 ~ 85°C	•		1550	1550
28	SFPG80		•		Single-mode	80 KM	0 ~ 70°C	•		1550	1550
29	SFPG110		•		Single-mode	110 KM	0 ~ 70°C	•		1550	1550
30	SFPG110T		•		Single-mode	110 KM	-40 ~ 85°C	•		1550	1550
31	SFPG120		•		Single-mode	120 KM	0 ~ 70°C	•		1550	1550
32	SFPG120T		•		Single-mode	120 KM	-40 ~ 85°C	•		1550	1550
33	SFPM20B1	•			Single-mode	20 KM	0 ~ 70°C	•	•	1310	1550
34	SFPM20B1T	•			Single-mode	20 KM	-40 ~ 85°C	•	•	1310	1550
35	SFPM20B2	•			Single-mode	20 KM	0 ~ 70°C	•	•	1550	1310
36	SFPM20B2T	•			Single-mode	20 KM	-40 ~ 85°C	•	•	1550	1310
37	SFPM40B1	•			Single-mode	40 KM	0 ~ 70°C	•	•	1310	1550
38	SFPM40B1T	•			Single-mode	40 KM	-40 ~ 85°C	•	•	1310	1550
39	SFPM40B2	•			Single-mode	40 KM	0 ~ 70°C	•	•	1550	1310
40	SFPM40B2T	•			Single-mode	40 KM	-40 ~ 85°C	•	•	1550	1310
41	SFPM60B1	•			Single-mode	60 KM	0 ~ 70°C	•	•	1310	1550
42	SFPM60B1T	•			Single-mode	60 KM	-40 ~ 85°C	•	•	1310	1550
43	SFPM60B2	•			Single-mode	60 KM	0 ~ 70°C	•	•	1550	1310
44	SFPM60B2T	•			Single-mode	60 KM	-40 ~ 85°C	•	•	1550	1310
45	SFPG050B1		•		Multi-mode	500 M	0 ~ 70°C	•	•	1310	1550
46	SFPG050B2		•		Multi-mode	500 M	0 ~ 70°C	•	•	1550	1310
47	SFPG10B1		•		Single-mode	10 KM	0 ~ 70°C	•	•	1310	1550
48	SFPG10B1T		•		Single-mode	10 KM	-40 ~ 85°C	•	•	1310	1550

SFP Transceiver Selection

No.	P/N	Speed			Type	Distance	Temp.	DDM	BIDI	Wave Length	
		100M	1G	10G						TX	RX
49	SFPG10B2		•		Single-mode	10 KM	0 ~ 70°C	•	•	1550	1310
50	SFPG10B2T		•		Single-mode	10 KM	-40 ~ 85°C	•	•	1550	1310
51	SFPG20B1		•		Single-mode	20 KM	0 ~ 70°C	•	•	1310	1550
52	SFPG20B1		•		Single-mode	20 KM	-40 ~ 85°C	•	•	1310	1550
53	SFPG20B2		•		Single-mode	20 KM	0 ~ 70°C	•	•	1550	1310
54	SFPG20B2T		•		Single-mode	20 KM	-40 ~ 85°C	•	•	1550	1310
55	SFPG40B1		•		Single-mode	40 KM	0 ~ 70°C	•	•	1310	1550
56	SFPG40B1T		•		Single-mode	40 KM	-40 ~ 85°C	•	•	1310	1550
57	SFPG40B2		•		Single-mode	40 KM	0 ~ 70°C	•	•	1550	1310
58	SFPG40B2T		•		Single-mode	40 KM	-40 ~ 85°C	•	•	1550	1310
59	SFPG60B1		•		Single-mode	60 KM	0 ~ 70°C	•	•	1310	1550
60	SFPG60B1T		•		Single-mode	60 KM	-40 ~ 85°C	•	•	1310	1550
61	SFPG60B2		•		Single-mode	60 KM	0 ~ 70°C	•	•	1550	1310
62	SFPG60B2T		•		Single-mode	60 KM	-40 ~ 85°C	•	•	1550	1310
63	SFPXG030			•	Multi-mode	300 M	0 ~ 70°C	•		850	850
64	SFPXG10			•	Single-mode	10 KM	0 ~ 70°C	•		1310	1310
65	SFPXG20			•	Single-mode	20 KM	0 ~ 70°C	•		1310	1310
66	SFPXG40			•	Single-mode	40 KM	0 ~ 70°C	•		1550	1550
67	SFPXG80			•	Single-mode	80 KM	0 ~ 70°C	•		1550	1550

✓ All SFP are with 1-Year Warranty