



## FEATURE HIGHLIGHTS

- 5x 10/100T(x) M12 connector
- IP67 protection – against water, dust, and oil
- Rugged M12 connectors for shock and vibration
- Deploy to harsh industrial environment
- Profinet Conformance Class A
- Support wide operating temperature (-40 to 75°C)

## DESCRIPTION

RPT-M1005-T-X2 provide 5 10/100 TX with M12 connectors for your industrial applications. The housing is water proof (IP67) and the device is design to operate in extreme operating temperature between -40 to 75 degree C.

RPT-M1005-T-X2 support power input variant between 12 to 48V, and its application has been successful in the processing & packaging factories and robotics factory . RPT-M1005-T-X2's compact and slim size with wall-mounting design provides a flat-type switch that can be easily fastened on a working bench or cabinet.

**SPECIFICATIONS**

<b>Technology</b>	
Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX
Processing Type	Store and Forward
<b>Switch Properties</b>	
Switch Fabric	1Gbps
Priority Queues	-
MAC Table Size	1K
Packet Buffer	448Kbits
<b>Interface</b>	
Network Connector	5x 10/100T(x) M12 Female D-coded 4-pole, auto negotiation speed duplex mode, auto MDI/MDI-X
LED Indicators	Per unit: PWR Ports: Link/Active(Green)
<b>Power Requirements</b>	
Operation Voltage	12-48VDC
Connection	M12 Male A-coded 5-pole
Power Consumption	2W
Protection	Overload Current Protected, Reverse Polarity Protected
<b>Mechanical Construction</b>	
Enclosure	Plastic
Protection Class	IP67
Dimensions	33x217x43 mm (WxHxD)
Weight	0.30 kg
Mounting	Wall Mounting Kits
<b>Environmental Limits</b>	
Operating Temperature	Extended: -40°C ~ 75°C (-40°F ~ 167°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Ambient Relative Humidity	5 to 95%, (Non-Condensing)

# RPT-M1005-T-X2 | Industrial 5 Port M12 Unmanaged Ethernet Switch

## SPECIFICATIONS

Regulatory Approvals	
EMI	FCC Part 15 Subpart B Class A
	CE EN 55032 Class A
EMS	IEC61000-4-2 (ESD)
	IEC61000-4-3 (RS)
	IEC61000-4-4 (EFT)
	IEC61000-4-5 (Surge)
	IEC61000-4-6 (CS)
Free Fall	IEC60068-2-32
Shock	IEC61373
Vibration	IEC61373
Green	RoHS Compliant
MTBF	>100,000 hours
Warranty	5 Years

## ORDERING INFORMATION

Model name	Description
RPT-M1005-T-X2	5 Port Industrial Unmanaged 10/100 M12 IP 67 Ethernet Switch

## DIMENSIONS

